

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Temperature Sensor**

with type designation(s)

MF19, MF20, TP2, TP3, TH3, TP8, TH8, TP11, TH11/TN4, TF4, TP4, TH4

Issued to

NORIS Automation GmbH
Nürnberg Bayern, Germany

is found to comply with

DNV GL rules for classification – Ships**Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Location classes:****Temperature B**
Humidity B
Vibration B
EMC A**Enclosure Required protection according to DNV Rules shall be provided upon installation on board.**This Certificate is valid until **2021-06-30**.Issued at **Hamburg** on **2017-05-04**DNV GL local station: **Augsburg**Approval Engineer: **Klaus-Peter Schröder**

Digitally Signed By: Rinkel, Marco

for **DNV GL**

Signing Date: 2017-05-11

Location: Hamburg - On behalf of

Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-005482-5**
 Certificate No: **TAA00000GW**
 Revision No: **1**

Product description

Temperature sensors and Thermowells as specified below:

Sensor types (Part 1)

Series MF19	MF19 -{d}-{e}-{g}-{k}	Pt100, Stern tube temperature
	MF19 -{d}-{e}-H{b}-{k}	NTC, Stern tube temperature

Sensor elements: Pt100 Class F0,3 (B) Range -25°C ... 100°C
 NTC "NORIS Standard" Range 0°C ... 70°C ; 40°C ... 100°C

Sensor lengths: Manufactured to customer requirements. (no standard lengths)
 {b} = Temperature range NTC
 {d} = Position sensor 1 (length L1)
 {e} = Position sensor 2 (length L2, does not apply for 1 sensor)
 {g} = Measuring circuit of Pt100 (does not apply for Pt100 2-Wire or NTC)
 {k} = Cable length (does not apply for standard length)

Series MF20	MF20 -{a}-{x}	Pt100, Bearing temperature
	MF20 -{a}H{b}-{x}	NTC, Bearing temperature

Sensor elements: Pt100 Class F0,3 (B) Range -25°C ... 120°C
 NTC "NORIS Standard" Range 0°C ... 70°C ; 40°C ... 120°C

Sensor lengths: Manufactured to customer requirements. (no standard lengths)
 {a} = Number of sensor elements (max. 3)
 {b} = Temperature range NTC
 {x} = special design

Series TP2	{a} TP2 {b}-{d}-{g}-{k}	Pt100, for protection tube
	{a} TP2 {b}0-{d}-{k}	Pt1000, for protection tube
Series TP3	TP3 {b}-{d}-{x}	Pt100, for protection tube
	TP3 {b}0-{d}-{x}	Pt1000, for protection tube
Series TH3	TH3 {b}-{d}-{x}	NTN, for protection tube
Series TP8	{a} TP8 {b}-{d}-{x}	Pt100, for protection tube
	{a} TPT8 {b}-{d}-{x}	Pt1000, for protection tube
Series TH8	{a} TH8 {b}-{d}-{x}	NTN, for protection tube
Series TP11	{a} TP11 {b}-{d}-{n}	Pt100, for protection tube
	{a} TPT11 {b}-{d}-{n}	Pt100, for protection tube
Series TH11	{a} TH11 {b}-{d}-{n}	NTN, for protection tube

Sensor elements: Pt100/Pt1000 Class F0,3 (B) Range -25°C ... 120°C (150°C, 200°C)
 NTC "NORIS Standard" Range 0°C ... 70°C ; 40°C ... 120°C

Immersion depth: Standard lengths 50, 56, 75, 100, 150, 200, 250mm

Protection tube (Thermowell)	MX2 -{c}-{d}		CuZn39 , max. 200°C
	MX5 -{c}-{d}		1.4305 , max. 200°C
	MX6 -{c}-{d}		1.4305 , max. 200°C
	MX13 -{c}-{d}	seawater resistant	2.1972 (CuNi10Fe)
	MX24 -{c}-{d}		CuZn39 , max. 200°C
	MX25 -{c}-{d}		1.4305 , max. 200°C
	MX34 -{c}-{d}		CuZn39 , max. 200°C
	MX37 -{c}-{d}		CuZn39 , max. 200°C

Job Id: **262.1-005482-5**
 Certificate No: **TAA00000GW**
 Revision No: **1**

	MX41 -{c}-{d}	1.4305 , max. 200°
	MX42 -{c}-{d}	1.4305 , max. 200°C

- {a} = Number of sensor elements (max. 2, does not apply for 1)
 {b} = Construction / Temperature range
 {c} = Thread
 {d} = Immersion depth (does not apply for standard length 56mm)
 {g} = Measuring circuit of Pt100 (does not apply for Pt100 2-Wire or NTC)
 {k} = Cable length (does not apply for standard length 2,3m)
 {n} = Connection
 {x} = Option for special design

Sensor types (Part 2)

Series TN4	{a} TN4 {b}- 0 -{d}-{k}	type K (NiCr-Ni), angled version for compression fitting
	{a} TN4 {b}- 1 -{d}-{k}	type K (NiCr-Ni), angled version for protection tube
	{a} TN4 {b}- 2 -{d}-{h}	type K (NiCr-Ni), connection head version for compression fitting
	{a} TN4 {b}- 3 -{d}-{h}	type K (NiCr-Ni), connection head version for protection tube
	{a} TN4 {b}- 4 -{d}-{k}	type K (NiCr-Ni), straight version for compression fitting
	{a} TN4 {b}- 5 -{d}-{k}	type K (NiCr-Ni), straight version for protection tube

Series TF4	{a} TF4 {b}- 0 -{d}-{k}	type J (Fe-CuNi), angled version for compression fitting
	{a} TF4 {b}- 1 -{d}-{k}	type J (Fe-CuNi), angled version for protection tube
	{a} TF4 {b}- 2 -{d}-{h}	type J (Fe-CuNi), connection head version for compression fitting
	{a} TF4 {b}- 3 -{d}-{h}	type J (Fe-CuNi), connection head version for protection tube
	{a} TF4 {b}- 4 -{d}-{k}	type J (Fe-CuNi), straight version for compression fitting
	{a} TF4 {b}- 5 -{d}-{k}	type J (Fe-CuNi), straight version for protection tube

Series TP4	{a} TP4 {b}- 2 -{d}-{h}	Pt100, connection head version for compression fitting
	{a} TP4 {b}- 0-2 -{d}-{h}	Pt1000, connection head version for compression fitting
	{a} TP4 {b}- 3 -{d}-{h}	Pt100, connection head version for protection tube
	{a} TP4 {b}- 0-3 -{d}-{h}	Pt1000, connection head version for protection tube

Series TH4	{a} TH4 {b}- 2 -{d}-{h}	NTN, connection head version for compression fitting
	{a} TH4 {b}- 3 -{d}-{h}	NTN, connection head version for protection tube

Sensor elements: type K (NiCr-Ni) Class 1 Range 0°C ... 800°C
 type J (Fe-CuNi) Class 2 Range 0°C ... 600°C
 Pt100 / Pt1000 Class F0,3 (B) Range -50°C ... 200°C ; 0°C ... 600°C
 NTC "NORIS Standard" Range 0°C ... 70°C ; 40°C ... 120°C

Immersion depth: Standard lengths 50, 75, 100, 150, 200, 250mm (max 200mm for Diesel exhaust)

Protection tube (Thermowell)	MX8 -{c}-{d}	medium mech. stress	1.4541 , max. 800°C
	MX9 -{c}-{d}	medium mech. stress, with neck tube	1.4541 , max. 800°C
	MX11 -{c}-{d}	seawater resistant	2.1972 (CuNi10Fe)
	MX26 -{c}-{d}	high mech. stress	1.4541 , max. 800°C
	MX27 -{c}-{d}	high mech. stress, with neck tube	1.4541 , max. 800°
Compression fitting	VS37 -{c}	heavy duty version	1.0718 / ISO4042-A2K

Job Id: **262.1-005482-5**
 Certificate No: **TAA00000GW**
 Revision No: **1**

- {a} = Number of sensor elements (max. 2, does not apply for 1)
- {b} = Construction / Temperature range
- {c} = Thread
- {d} = Immersion depth
- {h} = Option for connection head
- {k} = Cable length (does not apply for standard length)

Place of manufacture

NORIS Automation GmbH
 Muggenhofer Straße 95
 90429 Nürnberg
 Germany

Feßlerstraße 3
 22083 Hamburg
 Germany

Application/Limitation

The Type Approval covers hardware listed under Product description.
 When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL RU SHIP Pt.4 Ch.9 Sec. 1.
 Sensors longer than standard are to be clamped as found required.

Type Approval documentation

Sensor types (Part 1)

Data sheets	Technical details see drawings
-------------	--------------------------------

Drawing	MF19-...	60.231 (Rev. n / 22.09.1994)
	MF20-...	60.232 (Rev. 1 / 15.03.2017) 60.232.0 (Rev. 1 / 15.03.2017)
	T.2...	60.230 (Rev. 1 / 17.03.2017) 60.230.1 (Rev. 1 / 17.03.2017)
	T.3...	60.206 (Rev. 1 / 17.03.2017) 60.206.7 (20.09.1996) 60.206.51 (16.05.2002)
	T.8...	60.207.8 (Rev. 1 / 15.03.2017) 60.207.81 (Rev. 1 / 15.03.2017)
	T.11...	60.272.2 (Rev. 1 / 15.03.2017) 60.272.21 (Rev. 1 / 15.03.2017) 60.272.22 (Rev. 1 / 15.03.2017) 60.273.23 (Rev. 1 / 15.03.2017) 60.272.3 (Rev. 1 / 15.03.2017)
	MX2-...	60.206 (Rev. 1 / 17.03.2017) 60.206.7 (20.09.1996) 60.206.51 (16.05.2002)
	MX5-...	60.206 (Rev. 1 / 17.03.2017) 60.206.7 (20.09.1996) 60.206.51 (16.05.2002)
	MX6-...	60.230 (Rev. 1 / 17.03.2017) 60.230.1 (Rev. 1 / 17.03.2017)
	MX13-...	60.206 (Rev. 1 / 17.03.2017)

Job Id: **262.1-005482-5**
 Certificate No: **TAA00000GW**
 Revision No: **1**

		60.206.7 (20.09.1996) 60.206.51 (16.05.2002)
	MX24-...	60.207.8 (Rev. 1 / 15.03.2017) 60.207.81 (Rev. 1 / 15.03.2017)
	MX25-...	60.207.8 (Rev. 1 / 15.03.2017) 60.207.81 (Rev. 1 / 15.03.2017)
	MX34-...	60.272.2 (Rev. 1 / 15.03.2017) 60.272.21 (Rev. 1 / 15.03.2017) 60.272.22 (Rev. 1 / 15.03.2017) 60.273.23 (Rev. 1 / 15.03.2017) 60.272.3 (Rev. 1 / 15.03.2017)
	MX37-...	60.272.2 (Rev. 1 / 15.03.2017) 60.272.21 (Rev. 1 / 15.03.2017) 60.272.22 (Rev. 1 / 15.03.2017) 60.273.23 (Rev. 1 / 15.03.2017) 60.272.3 (Rev. 1 / 15.03.2017)
	MX41-...	60.272.2 (Rev. 1 / 15.03.2017) 60.272.21 (Rev. 1 / 15.03.2017) 60.272.22 (Rev. 1 / 15.03.2017) 60.273.23 (Rev. 1 / 15.03.2017) 60.272.3 (Rev. 1 / 15.03.2017)
	MX42-...	60.272.2 (Rev. 1 / 15.03.2017) 60.272.21 (Rev. 1 / 15.03.2017) 60.272.22 (Rev. 1 / 15.03.2017) 60.273.23 (Rev. 1 / 15.03.2017) 60.272.3 (Rev. 1 / 15.03.2017)

Test report	LGA No. 477 1245 (16.12.1997)
	NORIS isotemp.doc (11.12.1997)
	NORIS beschlkl.doc (11.12.1997)
	NORIS waermepre.doc (11.12.1997)
	NORIS kaeltepre.doc (11.12.1997)
	NORIS hochsgp.doc (11.12.1997)
	BMP 1/96, NORIS mf201112.doc (23.01.1996) included documents: vibration, dry heat, humidity, insulation, high voltage

Sensor types (Part 2)

Data sheets	Technical details see drawings
-------------	--------------------------------

Drawing	T.4...-0-...	60.243.422 (Rev. e / 16.06.2016)
	T.4...-1-...	60.244.121 (Rev. g / 16.06.2016) 60.244.122 (Rev. g / 16.06.2016) 60.244.221 (Rev. d / 01.07.2016) 60.244.222 (Rev. d / 01.07.2016)
	T.4...-2-...	60.243.431 (Rev. g / 01.06.2016) 60.243.432 (Rev. g / 01.06.2016) 60.243.433 (Rev. g / 01.06.2016) 60.243.434 (Rev. g / 01.06.2016)
	T.4...-3-...	60.244.131 (Rev. m / 28.06.2016) 60.244.132 (Rev. m / 28.06.2016) 60.244.133 (Rev. m / 24.06.2016) 60.244.134 (Rev. m / 28.06.2016) 60.244.231 (Rev. a / 04.07.2016) 60.244.232 (Rev. a / 04.07.2016)
	T.4...-4-...	60.243.411 (Rev. c / 17.06.2016) 60.243.412 (Rev. c / 17.06.2016)

Job Id: **262.1-005482-5**
Certificate No: **TAA00000GW**
Revision No: **1**

	T.4...-5-	60.244.111 (Rev. c / 29.06.2016) 60.244.112 (Rev. c / 29.06.2016) 60.244.211 (Rev. a / 04.07.2016) 60.244.212 (Rev. a / 04.07.2016)
	MX8-...	60.241.121 (Rev. c / 12.05.2016)
	MX9-...	60.241.221 (Rev. a / 12.05.2016)
	MX11-...	60.241.141 (Rev. b / 12.05.2016)
	MX26-...	60.241.131 (Rev. b / 12.05.2016)
	MX27-...	60.241.231 (Rev. a / 12.05.2016)
	VS37-...	60.241.431 (Rev. a / 12.05.2016)

Test report	RMS No. 48/92 (10.06.1986)
	RMS No. 2-03/95 (13.03.1995)
	RMS No. 3-03/95 (13.03.1995)
	RMS No. 03-05/2000 (06.06.2000)

Certificate retention survey report for A-10859, DNV Essen 2012-06-29
Type Approval Assessment Report (01.07.2016)

Tests carried out

Applicable tests according to Class Guideline DNVGL-CG-0339, Edition November 2015.

Marking of product

The products to be marked with:

- device name
- manufacturer name
- serial number.

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
 - Inspection of factory samples, selected at random from the production line (where practicable)
 - Review of production and inspection routines, including test records from product sample tests and control routines
 - Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
 - Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
 - Ensuring traceability between manufacturer's product type marking and the type approval certificate
- Periodical assessment is to be performed at renewal and at least once in the period of the validity of this certificate.

END OF CERTIFICATE