

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Control levers**with type designation(s)  
**NORISYS 4 LA4**

Issued to

**Noris Automation GmbH**  
**Rostock, Germany**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

<b>Temperature</b>	<b>D</b>
<b>Humidity</b>	<b>B</b>
<b>Vibration</b>	<b>A</b>
<b>EMC</b>	<b>B</b>
<b>Enclosure</b>	<b>C (front side)</b>

Issued at **Hamburg** on **2020-01-28**for **DNV GL**This Certificate is valid until **2025-01-14**.DNV GL local station: **Hamburg CMC**Approval Engineer: **Holger Jansen**

---

**Joannis Papanuskas**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



## Product description

The NORISYS 4 Control Lever Devices LA4 are equipped with an interface electronic which provides signals and communication interfaces for the remote control system designed for main propulsion plants.

Common characteristic:

Supply Voltage: 24 Vdc  
Current consumption: 0.15 .. 1,5A according to level of equipment

### NORISYS 4 LA4 Control Lever

Nomenclature a-b-c-d-e-f-g-h-i

- a: Base type: LA4: Azimuth lever with rotational and thrust setpoint value
- b: Scale orientation: FWD: Forward oriented installation  
AFT: Astern oriented installation
- c: Rotary scale: 180: Scale marking for 90° in CW/CCW, turning range of 180°  
360: Scale marking for 180° in CW/CCW, endless turning range (360°)  
C: Customer-specific scale and turning range, e.g. ± 35°
- d: Scale design: /0-10  
/10-0-10
- e: Scale subdesign: blank: No extra scale design is used  
ORD: Scale design with order steps
- f: Signal processing: E1: Signal processing electronic, 2xCANbus  
2x 4..20mA OUT, 2x Digital IN, 1x PWM IN, LED band  
E2: Signal processing electronic, 2xCANbus, 1x RS-485  
1x Digital IN, 1x Digital OUT, 1x PWM IN, LED band
- g: Illuminaton: IL4: Rotation scale illumination and alignment cross  
IL5: Control head/Rotation scale with scale illumination and position indicator
- h: Options: ESS: Electrical shaft system  
MLP: Mechanical lock points (not applicable with ESS option)
- i: Layout: 192x192:

## Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems.

## **Type Approval documentation**

### **Drawings:**

Norisys Control Lever System Manual Ver. 1.23, No. NAR-KD-0111-1-en, 2019-11-27  
Firmware element ExtensionBus, Firmware routines desc Ver. 1.03, No NAR-PD-0110-1-en, 2011-10-27  
Norisys 4 Control Lever System LA4, Overview Suppliers Ver. 1.01, No. NAR-PD-0111-11-en, 2013-11-27  
Noristar Control Lever LS4/LA4/LTK4 Firmware Desc. Ver. 2.5.0, No. NAR-PD-0111-2-en, 2019-10-10  
Norisys Control Lever System LS4/LA4/LTK4, Hardware Desc. Ver.1.01, No. NAR-PD-0111-1-en, 2019-09-26

### **Noris Wiring Diagrams:**

SAR45-h, 2017-05-05, SAR46-e, 2019-11-09, SAR60-e, 2012-08-17, SAR85-b, 2018-01-29,  
SAR86-e, 2017-05-22, SAR88-d, 2015-12-15, SAR98-b, 2016-11-09

### **Noris Mechanical Documents:**

092.037.03.100A, 2014-12-04, 092.017.03.218.A, 2013-06-21,  
092.037.03.408.A, 2013-05-03, 092.004.03.200.A, 2011-12-19

Test reports : Teseq No.D/13/4085/11, 2013-12-20

Treo No. 023-14 Ver.2, 2014-04-29; Treo No. 255-13 Ver.1, 2013-11-13

Treo No. 288-13 Ver.1, 2014-03-07

TüV No. 21215783001, 2014-04-23

Test protocol: Noris No. NAR-PB-0111-2-en Ver. 1.06, 2014-05-05

Type Approval Assessment Report 2019-12-20

## **Tests carried out**

Applicable tests according to DNV GL Class Guideline CG0339, November 2016.

## **Marking of product**

The products to be marked with:

- Noris Automation GmbH
- Model name
- Serial number

## **Periodical assessment**

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE